



VACUUM LIQUID FERTILIZER SPREADER

DLVF



SPECIFICATIONS

- Ideal for industrial effluents transportation.
- High efficiency for suction and distribution of liquid organic manure from pigs and cattle.
- Ideal for cleaning septic tanks and transportation of organic liquid waste.
- Ideal for water transportation for supplying sprayers, and for assistance in machine and shed washing.
- High-performance vacuum and pressure pump, which enables uninterrupted work.
- It provides greater efficiency in loading and unloading, and it does not pollute the environment.
- Easy operation and low maintenance cost.
- Options for 4" or 6" side-loading valve with manual opening, wheels, tires, hydraulic brake on 2 or 4 wheels, cannon kit with 60.3 mm output, irrigation kit with 2" hose, and 12 m hose irrigation kit.
- V-rod connected to the axle to reduce fatigue on the tank.
- Rear lid with total aperture.
- With wave breaker.
- External PU paint and varnish, and internal epoxy paint.



Our technology for your business



AVAILABLE IN THE COLORS:



VACCUM LIQUID FERTILIZER SPREADER

Sizes	4.000 / 6.000 / 8.000 / 10.000 / 12.000 L
Pumps	4.000 - 4.300 L/min. ou 6.500 - 7.000 L/min.
Rear valve	4" passage or 6" passage
Rod structure	1/4" carbon steel plate
Tank structure	3/16" carbon steel plate



Contact us: Rodovia Frei Belmiro Brondani, S/N - SC 355 - km 94.
Interior, Treze Tílias, SC. (49) 3090.0735 | (49) 99963.1091
implementos@farenzena.com.br

